ARMASHEILD

What is it?

ARMASHEILD is a single component silver coating. It is made up of various materials, chemically inert reinforcement fillers, oils, water repellent chemicals and oxidation inhibitors.

What is it for?

ARMASHEILD is specially formulated to give an anti corrosive protection to the top surface of any buses, trains, or any commercial vehicles. Apart from providing anti corrosive properties it also provides water proofing which prevents any seepage of water. Along with this it has also has heat reflecting properties and helps to reduce the temperature of the surface below where it is applied by 2-3 degrees Celsius.

How to use ARMASHEILD

Make sure the surface is dry and free from loose dust particles, rust and scales before application. Apply uniformly with a clean paint brush Allow 4 to 8 hours for touch set dryness and 24 to 48 hours before handling.

CONFIRMING TO	HEAT TEST, COLD TEST, FLEXIBILITY AND
	ADHESION TEST AS PER A-1.6 OF IS: 1322 OF 1982.
	ANTI CORROSIVE -SALT SPRAY TEST
	HEAT REFLECTING TEST
COLOUR	SILVER
PHYISCAL APPERANCE	HOMOGENOUS SILVER LIQUID
FINISH	SMOOTH AND GLOSSY
APPLICATION	BY BRUSH
DRYING TIME	8 HRS TOUCH DRY AND 24 HRS FOR HARD
	DRY UNDER NORMAL CONDITIONS
NUMBER OF COATS	2 COATS MINIMUM
COVERING CAPACITY	1.25 TO 2 SQMTRS P/KG/COAT DEPENDING ON SURFACE
PACKING	20 KGS

Important

- 1. Open ARMASHEILD drum and stir the contents with a rod till it is of uniform consistency.
- 2. Keep ARMASHEILD away from sunlight.
- 3. Avoid storing ARMASHEILD in areas with high temperature.
- 4. Do not leave drums open after use.
- 5. Do not use any thinner.





