

# BIO-WASH

BIO-WASH is a water thinnable solution used for treating the exterior walls and surfaces. BIO-WASH is to be used as a pre treatment wash for exterior walls and surfaces which will help to resist algal and fungal growth.

## FEATURES:

BIO-WASH contains special chemicals which resists algal and fungal growth.

**NATURE:** clear liquid

**BASE:** water

**COLOUR:** slight reddish

**FLOW:** smooth and consistent

**MODE OF APPLICATION:** by brush preferably. Can also be applied by spray gun

**DRYING TIME:** approx 1 hour depending on climatic conditions

## SURFACE

BIO-WASH can be applied by brush or spray gun to any cement/sand renderings.

## SURFACE PREPARATION

The structure should be free of faults specially which leads to moisture penetration, if there are any they should be rectified. All surfaces should be clean and dry. This is very important in case of new buildings.

Firstly remove all loose particles, dust, dirt, algal and fungal with the help of a stiff brush. Secondly wash the surface with water and then allow it to dry sufficiently. All cracks, voids and damages on the wall should be repaired before the application of BIO-WASH.

## MIXING RATIO

Mix one part of BIO-WASH with one part of clean portable water i.e. 1:4 and stir properly.



## METHOD OF APPLICATION

After the cleaning the wall/surfaces, allow it to dry completely. Then apply BIO-WASH on it with brush or spray gun. Leave it for 24 hrs. The surface is been treated which will avoid the future growth of algal and fungal. Now the surface is ready for application of any type of paint.

BIO-WASH can be used on roofs or on walls. It can also be used on old or new surfaces/ walls even where there in no algal or fungal growth.

## COVERAGE

The coverage of BIO-WASH depends upon the condition of the surface/wall and also on the method of application.

APPROX coverage: 90 to 95 sq.mtrs. Per litre.

## PACKING

BIO-WASH is available in 30 lt and 5 lt jerry cans.

