

SATIN TOUCH

Luxury emulsion

As the name suggests satin touch provides a rich, smooth and luxurious finish on your walls. Satin touch luxury emulsion also provides fungus and stain resistance. Walls which are painted with satin touch are easy to clean and maintain, with a rich look for many years.

APPLICATION

Phoenix Satin touch can be applied to all kinds of interior walls, ceilings, asbestos sheet etc.

RECOMMENDED APPLICATION

2 Coats for old walls and 3 coats for newly plastered walls

SURFACE PREPARATION

In case of old painted walls, sand the walls with emery paper. Remove loose particles, and fill any dents or cracks with Shellcare putty. Allow it to dry and then apply Primecoat. In case of new plastered walls prime the surface by applying 2 coats of Primecoat

APPLICATION

Apply the 1st coat of Satin touch luxury emulsion by mixing it with water. Mix 1ltr of Satin touch luxury emulsion with max 250-500ml of water, do not over dilute it. Allow it to dry for 6-8 hrs. Then apply the 2nd coat of Satin touch by mixing in the same ratio and again allow it to dry for 6-8 hrs. Stir thoroughly before using it.

PACKING

Available in 20 ltrs, 10 ltrs, 4 ltrs and 1 ltr plastic tins.

ENVIRONMENT & SAFETY

Satin touch luxury emulsion is environment friendly as it is both non-toxic and non-flammable. It is hygienic as it does not pollute the air. Splashes of blossom in contact with skin should be immediately washed with water for easy removal. If it comes in contact with eyes wash thoroughly with plenty of water. If irritation persists, obtain medical help.

