

# PRIMECOAT

## *Interior Primer (Water Thinnable)*

Primecoat is an interior wall primer (water Thinnable) which can be used for priming interior plastered walls, cement and asbestos sheets.

### FEATURES

- Is a primer for interior walls
- Has high covering capacity
- Has a very bright white appearance
- Has a very nice brushability
- Good sealing capacity

### USAGE

- For interior walls
- For interior plastered surfaces

### SURFACE PREPARATION

Allow the new masonry surface to dry out completely. Remove loose particles if any. Before applying PRIMECAOT apply 1 coat of Shellcare putty. Allow it to dry and then sand it with emery paper 180. Then apply 1st coat of PRIMECAOT and allow it to dry for 4-6 hrs and then apply the second coat. In case of old walls, sand the wall with emery paper 180. Fill dents cracks if any with Shellcare putty. Allow it to dry and then apply 2 coats of PRIMECAOT at intervals of 4-6 hrs.

### APPLICATION

Apply it by brush only. The time interval between two coats of PRIMECAOT should be 4-6 hrs.

### THINNING

Mix PRIMECAOT with water in order to achieve brushability. Please do not over dilute it.

### PACKING

Available in 20 ltrs, 10 ltrs, 4 ltrs and 1 ltr tins.

### ENVIRONMENT & SAFETY

PRIMECOAT is environment friendly as it is non- toxic and non-flammable. It is hygienic as it does not pollute the air. Splashes of PRIMECOAT in contact with skin should be immediately washed with water for easy removal. If it comes in contact with eyes wash thoroughly with plenty of water. If irritation persists, obtain medical help.

