

PRIMECOAT XT

Exterior Water Thinnable Primer

PRIMECOAT XT is an exterior water thinnable primer. It can be used as base coat before applying any kind of acrylic paint. It is basic formulated to increase the life of the paint applied. It helps to provide better hiding power to the acrylic paint applied.

TECHNICAL DATA:

FEATURES:

Easily Brushable "Excellent Binding Strength" Recommended for Exterior Surfaces "Based on Pure Acrylic Emulsions" Good Hiding Power

AREAS OF APPLICATION:

Primer coat for any exterior emulsion.

DIRECTIONS FOR USE. SURFACE PREPARATION

APPLICATION:

Newly plastered surface should be fully cured and allowed to dry. Ensure that the surface to be painted is free from dirt, dust, grease, and loose paint algae fungus or any other powdery materials. Surfaces previously coated with cement paint should be wire brushed, washed thoroughly with water and allowed to dry. PRIMECOAT XT should be mixed with water in ratio 1ltr of PRIMECOAT XT with 500-700 ml of water max. Allow it to dry for 6-8 hrs. 2nd coat should be applied by mixing water in the same ratio. After 6-8 hrs you can apply any exterior emulsion of your choice.

PACKING

Available in 20 ltrs, 10 ltrs, 4 ltrs and 1 ltr plastic tins.

ENVIRONMENT & SAFETY

PRIMECAOT XT is environment friendly as it is both non- toxic and non-flammable. It is hygienic as it does not pollute the air. Splashes of blossom in contact with skin should be immediately washed with water for easy removal. If it comes in contact with eyes wash thoroughly with plenty of water. If irritation persists, obtain medical help.

Material Handling:

1. Store in a cool & dry place.
2. Stir well before use.

