

SHELLCARE WALL PUTTY

Luxury emulsion

Shellcare wall putty is a water resistant white cement based putty for concrete /mortar walls and ceilings. Shellcare wall putty can be applied even on moist surfaces (internal/external). Shellcare wall putty has more adhesive strength, durability and increases the life of paints. Shellcare wall putty though white cement based, does not require water curing. It renders a smooth and durable surface suitable for all kind of paints.

FEATURES

- Being a cementitious material it has better adhesiveness and durability.
- It does not require water curing.
- It is water resistant and can be applied on moist surfaces.
- No need to apply any kind of primer on it.
- Any kind of paint or distemper can be applied on it.
- Applicable on both interior and exterior surfaces.
- It can be applied on sued surfaces after proper preparation.
- It contains fungicides to prevent the growth of fungus on its surface.
- It is in dry powder form and does not produce any kind of unpleasant smell at the time of application.
- Water requirement is 40-50%. (For 1 kg of material 400-500 ml water is needed.)
- Its coverage area on normal mortar wall is 50-55 sq.ft/Kg in single coat of 0.5-1.0 mm thickness and 22 to 25 sq.ft/ kg. In double coat of 1.0 to 1.5 mm. Thick.
- Its pot life is 3 hours for better results it should be used within 2 hours of preparation.

APPLICATION

- Before applying Shellcare wall putty remove all the loosely adhering material from the wall surface with the help of a sand paper, putty blade or wire brush.
- Moisten the walls with sufficient quantity of water.
- Mix the ready mix putty with 40-50% water slowly to make a workable paste. Continue the mixing of paste for 10-15 minutes and add more water if required.
- After that apply the first coat of putty on already moistened wall surface from bottom to upward direction uniformly with the help of putty blade.
- Always prepare a required quantity of putty and use it within 3 hours of mixing water.
- After drying of first coat of putty just rub the surface gently with hand to remove any loose sand particles.



- Allow the surface to dry preferably for overnight.
- The total thickness of the coats should limit to maximum 1.5 mm.
- Leave the surface to dry preferably for overnight.
- Before applying any kind of paint/ distemper level the walls/ ceilings with fine water proofing emery paper of 320 no, to remove unevenness and get a glossy white surface.

PRECAUTIONS

- It contains non-toxic materials but still a care should be taken to avoid dust inhalation while mixing and handling powdered putty. In case of contact with eyes or mouth, wash with plenty of water.
- Keep it in a dry place.
- Keep out of reach from children.

PACKING

SHELLCARE wall putty is available in 20 kg packing.

Shelf life: Six months.

